



TRAILER GENERAL SPECIFICATIONS (AS SHOWN):

TIRES:	(12) 255/70R22.5 LOW PROFILE	GOOSENECK:	MECHANICAL REMOVABLE
WHEELS:	(12) 22.5x8.25 STEEL DISC	DECK:	FLAT LEVEL - TELESCOPIC
BRAKES:	16 1/2"x7" AIR	BOGIE:	FIXED TWO AXLE WITH OPTIONAL 3RD AXLE PIN ON
AXLES:	(3) 25,000# CAP. (NOMINAL)	FRAME:	4-BEAM CONSTRUCTED T-1 COMBINATION FABRICATED STEEL
SUSPENSION:	AIR-RIDE W/AUTOMATIC & MANUAL CONTROLS	PAINT:	SHOT BLAST AND PRIME COAT COLOR PLEASE ADVISE
LIGHTS:	D.O.T. 12 VOLT 7 WAY-CONNECTOR SEALED BEAM LED SYSTEM		
LASHING RINGS:	9 PER SIDE (18 TOTAL)		TRAILER IS 8'-6" WIDE

\* WHEN THE TRAILER IS EXTENDED, THE LOAD ITSELF WILL BE REQUIRED TO SUPPORT THE DECK BY MEANS OF STRAPS, CHAINS, ETC. TO KEEP THE DECK FROM DROPPING BELOW ITS LEVEL CONDITION

ALL VERTICAL DIMENSIONS REFER TO A LOADED TRAILER

FONTAINE SPECIALIZED  
SPRINGVILLE, AL.

PART NAME:  
RENEGADE LXTN40

				DRAWN	DATE	CHECKED	DATE
*	*****g	***	**/**/**	GB	8/2/12		
REV.#	DESCRIPTION CHANGE	BY	DATE	UNLESS OTHERWISE SPECIFIED		FRACTIONS - ±1/16" ANGLES - ±0.5" 2 PLACE DEC - ±0.03" 3 PLACE DEC - ±0.005"	
				DIMENSIONS IN INCHES		SCALE: NONE NEW ASSY.: STD	

SIZE	PART NO.:	REVISION:
B	BTS-6058	0